NSN 4820-01-511-0029

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-511-0029

view Crimie at https://derobase	group.com/nan//4020-01-311-0023
Body Material:	
Copper alloy	
Body Style:	
Straight thru	
Furnished Items:	
Union nut and tailpiece	
Media For Which Designed:	
Water	
First End Connection Type:	
Unthreaded internal tube	
First End Style Designator:	
Socket	
First End Outside Diameter T	ube Accommodated:
1.500 inches	
Second End Relationship Wit	th First End:
Not identical	
Second End Connection Type	e:
Unthreaded internal tube	
Second End Style Designator	r:
Socket	
Second End Outside Diamete	er Tube Accommodated:
1.250 inches	
Face To Face Distance:	
11.000 inches	
Flow Control Device:	
Diaphragm	
Flow Control Device Material	:
Rubber, buna-n	
End Connection Quantity:	
2	
Valve Discharge Flow Rate:	
22.0 gallons per minute	
Regulation Type:	
Automatic single stage	
Maximum Inlet Pressure Ratio	ng:
150.0 pounds per square inch	
Tempurature Rating:	
160.0 degrees fahrenheit	

Product Name:

1-1/2 x 1-1/4 mesurflo automatic balancing valve with union ends and stainless steel tail pieces

Special Features:

This valve has bronze union nuts and 304l stainless steel tail pieces.

NSN 4820-01-511-0029

Calibrated Flow Valve - Page 2 of 2



Test Data Document:

81349-mil-s-901c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

he			

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100