

View Online at <https://aerobasegroup.com/nsn/4820-01-512-0823>

Pipe Size Accommodated:

6.321 inches 1st end

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Retaining screw

Bolt Hole Quantity:

24 all ends

Maximum Operating Temp:

160.0 degrees fahrenheit 3rd response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

10.125 inches all ends

Thickness:

1.188 inches all ends

Bolt Circle Diameter:

8.875 inches all ends

Flange Face Design:

Plain all ends

Product Name:

6" wog 250psi flanged y-pattern bronze globe valve

Special Features:

Flange face to face 17.0 in; flanges pre-drilled w/ 8-0.688" holes and 4-0.625-11 unc-2b holes on 8.875" b.C.; valve weight full assembled 200 lbs.

Material:

Rubber synthetic flow control device

Material Specification:

Mil-p-24503, type 2, cl 2, gr n. Die formed military specification single material response packing

Media For Which Designed:

Oil 1st response

Style Designator:

Err-090

Test Data Document:

80064-803-1385623 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-p-24503 spec.