

View Online at <https://aerobasegroup.com/nsn/4820-01-512-9969>

Pipe Size Accommodated:

0.555 inches 1st end

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Minimum Operating Temp:

-20.0 degrees fahrenheit

End Application:

Angle valve

Connection Style:

Socket err-100

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal pipe 1st end

Thready Qty Per Inch (tpi):

18 2nd end

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Thread Size:

0.562 inches 2nd end

Product Name:

250 angle shutoff valve, 6000 p.S.I. (414 bars), cat. 381-1-va.

Special Features:

Angle, shutoff valve with fittings. Recommended for water, oil, or gas service. This valve h.P. Hydraulic and pneumatic.

Material:

Steel comp 316 stem

Material Specification:

P-3086 plastic polyamide (nylon) military specification single material response flow control device

Style Designator:

Err-090

Test Data Document:

81349-mil-s-901d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt 2nd end

Furnished Items And Quantity:

1 handwheel and 2 tailpiece

Specification Data:

81349-mil-v-24109a government specification

Specification Or Standard:

381-1-va assembly

Departure From Cited Document:

Modified with tailpieces and union nuts.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-r-83248 spec.