# NSN 4820-01-514-1698

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-514-1698

Pipe Size Accommodated:

5.000 inches all ends

**Flow Control Device:** 

Disk

### Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Bolted

#### **Disk Loading Method:**

Spring

### Renewable Seat Ring Type:

Threaded

#### Maximum Operating Temp:

425.0 degrees fahrenheit single response

#### **Connection Style:**

Plain (tube) err-100

### Valve Operation Method:

Automatic

### **Connection Type:**

Butt weld pipe all ends

# Adjustable Pressure Range:

+33.0/+50.0 pounds per square inch

## Maximum Operating Pressure:

100.0 pounds per square inch single response

#### **Opening Pressure Setting:**

40.0 pounds per square inch

#### Material:

Nickel alloy flow control device

# Material Specification:

Qq-n-281 federal specification single material response stem

#### Media For Which Designed:

Water, salt single response

### Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A046b0

# NSN 4820-01-514-1698

Safety Relief Valve - Page 2 of 2

# Mil-std (military Standard):

Mil-b-16541 spec.

