

View Online at <https://aerobasegroup.com/nsn/4820-01-514-4445>

Thread Direction:

Right-hand all ends

End Application:

Cooperative e

Connection Style:

Plain (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe all ends

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

18 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Product Name:

Check valve

Special Features:

O-ring material ethylene propylene rubber iaw ams 7262 or equivalent; deflector cap material polyethylene material; cracking pressure -001.150 psi, -002.350 psi; temperature: -40 to 150 deg. C with standard ethylene propylene seals; flow coefficient: .35; length: 1.62 inches; hex" 9/16.

Material:

Stainless steel body

Material Specification:

Astm a276 assn standard single material response body

Media For Which Designed:

Water, fresh single response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Straight thru

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0