NSN 4820-01-514-5649

Compressed Gas Regulator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-514-5649

| 3 F |
|---|
| End Application: |
| Valve reg fdpress gas o.25in 4324301-01-0xe |
| Maximum Delivery Pressure: |
| 400.0 pounds per square inch |
| Mounting Method: |
| Cylinder |
| Mounting Position: |
| Left side |
| Stage Type: |
| Double |
| Inlet Fitting Connection Type: |
| Threaded internal pipe |
| Err Default: |
| Err default |
| Outlet Fitting Thread Direction: |
| Right-hand |
| Criticality Code Justification: |
| Zzzy |
| Delivery Pressure Type: |
| Adjustable |
| Err Default: |
| Err default |
| Outlet Fitting Connection Type: |
| Threaded internal pipe |
| Outlet Fitting Thread Size: |
| 0.250 inches |
| Inlet Indicator Type: |
| Dial pressure gage |
| Outlet Indicator Type: |
| Dial pressure gage |
| Special Features: |
| Requested name, regulator cartridge |
| Reference Number Differentiating Characteristics: |
| Cleaning and packing per mil-std-1330d |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A514u0