

View Online at <https://aerobasegroup.com/nsn/4820-01-517-2823>

Thread Class:

2b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

100.0 degrees fahrenheit single response

End Application:

Electronic cooling water skid

Connection Style:

Plain, optional end (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal tube all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

18 all ends

Maximum Operating Pressure:

15.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Opening Pressure Setting:

0.5 pounds per square inch

Outside Diameter Tube Accommodated:

0.750 inches all ends

Product Name:

Universal low pressure check valve

Special Features:

Next higer assembly: 55836 piping assembly v1 to cv1, b2 to cv2; 55839 piping assembly, full flow particulate assembly

Material:

Stainless steel

Material Specification:

Pcaf00 national specification single material response seat

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0