

View Online at <https://aerobasegroup.com/nsn/4820-01-517-2823>

**Thread Class:**

2b all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Disk Loading Method:**

Spring

**Renewable Seat Ring Type:**

Pressed-in

**Maximum Operating Temp:**

100.0 degrees fahrenheit single response

**End Application:**

Electronic cooling water skid

**Connection Style:**

Plain, optional end (pipe) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded internal tube all ends

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

18 all ends

**Maximum Operating Pressure:**

15.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Opening Pressure Setting:**

0.5 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.750 inches all ends

**Product Name:**

Universal low pressure check valve

**Special Features:**

Next higer assembly: 55836 piping assembly v1 to cv1, b2 to cv2; 55839 piping assembly, full flow particulate assembly

**Material:**

Stainless steel

**Material Specification:**

Pcaf00 national specification single material response seat

**Style Designator:**

Straight thru

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0