NSN 4820-01-517-5830

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-517-5830

| Pipe Size Accommodated: | | | | | |
|---|--|--|--|--|--|
| 0.250 inches all ends | | | | | |
| Thread Class: | | | | | |
| 2b 2nd end | | | | | |
| Thread Direction: | | | | | |
| Right-hand 1st end | | | | | |
| Flow Control Device: | | | | | |
| Stem | | | | | |
| Bonnet Type: | | | | | |
| Inside screw | | | | | |
| Bonnet Attachment Method: | | | | | |
| Integral | | | | | |
| End Application: | | | | | |
| Reverse osmosis water purification system | | | | | |
| Connection Style: | | | | | |
| G9 plain, optional en (pipe) 2nd end | | | | | |
| Valve Operation Method: | | | | | |
| Manual | | | | | |
| Connection Type: | | | | | |
| Threaded internal pipe 2nd end | | | | | |
| Features Provided: | | | | | |
| Bonnet packing | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 18 1st end | | | | | |
| Maximum Operating Pressure: | | | | | |
| 6000.0 pounds per square inch single response | | | | | |
| Thread Size: | | | | | |
| 0.250 inches 2nd end | | | | | |
| Material: | | | | | |
| Stainless steel flow control device | | | | | |
| Material Specification: | | | | | |
| Ptfe mfr ref single material response packing | | | | | |
| Media For Which Designed: | | | | | |
| Liquid 1st response | | | | | |
| Style Designator: | | | | | |
| Err-090 | | | | | |
| Thread Series Designator: | | | | | |
| Nptf 2nd end | | | | | |
| Furnished Items And Quantity: | | | | | |
| 1 handle | | | | | |
| Shelf Life: | | | | | |
| N/a | | | | | |

NSN 4820-01-517-5830

Globe Valve - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A046b0