NSN 4820-01-517-6081

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-517-6081

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Class:
2b 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
10.2 gallons per minute
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
406.0 degrees fahrenheit single response
End Application:
Reverse osmosis water purification unit, 3000 gal/day, model rodm-3
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
14 2nd end
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Opening Pressure Setting:
150.0 pounds per square inch
Material:
Stainless steel
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-517-6081

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0