NSN 4820-01-518-2438

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-518-2438

Flow Control Device: Spool Maximum Operating Temp: 200.0 degrees fahrenheit single response Minimum Operating Temp: -65.0 degrees fahrenheit Connection Style: Plain, optional end (pipe) all ends
Maximum Operating Temp: 200.0 degrees fahrenheit single response Minimum Operating Temp: -65.0 degrees fahrenheit Connection Style: Plain, optional end (pipe) all ends
200.0 degrees fahrenheit single response Minimum Operating Temp: -65.0 degrees fahrenheit Connection Style: Plain, optional end (pipe) all ends
Minimum Operating Temp: -65.0 degrees fahrenheit Connection Style: Plain, optional end (pipe) all ends
-65.0 degrees fahrenheit Connection Style: Plain, optional end (pipe) all ends
Connection Style: Plain, optional end (pipe) all ends
Plain, optional end (pipe) all ends
Value Operation Mathed
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Opening Pressure Setting:
2.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Product Name:
Soft seat republic check valve
Material:
Steel comp 303 body
Media For Which Designed:
Hydraulic fluid, petroleum base 2nd response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A530b0