

View Online at <https://aerobasegroup.com/nsn/4820-01-521-0018>

Body Material:

Bronze, astm b61

Body Style:

Straight thru

Stem Material:

Nickel copper alloy

Media For Which Designed:

Water

First End Connection Type:

Unthreaded internal pipe

First End Style Designator:

Socket

First End Pipe Size Accommodated:

0.500 inches

Seat Material:

Nickel copper alloy

Face To Face Distance:

9.500 inches

Flow Control Device:

Disk

Flow Control Device Material:

Rubber, buna-n

End Connection Quantity:

2

Renewable Seat Ring Type:

Retaining ring

Outlet Pressure Range:

+5.0/+60.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Stem Design:

Single seat

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

250.0 pounds per square inch

Filter:

Not included

End Application:

W/s nimitz

End Connection Specification/std:

5371-18-031-3859

Valve Size:

0.500 inches

Product Name:

Pressure reducing valve

Special Features:

Manufacturer identifies this valve as 1/2" style h sea water pressure reducing valve per mil-v-2042 type ii 250 lb. End connections are union end/tailpieces with 1 groove. Drawing note 7: o-rings and retaining rings provided only when specified on order.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100