

View Online at <https://aerobasegroup.com/nsn/4820-01-525-2007>

**Body Material:**

Bronze, astm b61

**Body Style:**

Straight thru

**Stem Material:**

Nickel copper alloy

**Furnished Items:**

Union nut and tailpiece w/grooves

**Media For Which Designed:**

Water, fresh

**First End Connection Type:**

Unthreaded internal pipe

**First End Style Designator:**

Reduced socket with one brazing ring

**First End Pipe Size Accommodated:**

1.000 inches

**Second End Relationship With First End:**

Identical

**Flow Control Device:**

Disk

**Flow Control Device Material:**

Rubber, buna-n

**End Connection Quantity:**

2

**Outlet Pressure Range:**

+25.0/+60.0 pounds per square inch

**Regulation Type:**

Automatic single stage

**Valve Loading Method:**

Spring

**Outlet Pressure Setting:**

40.000 pounds per square inch

**End Application:**

Cvn 77

**End Connection Specification/std:**

Mil-v-1183 with sbue 250 class

**Valve Size:**

1.000 inches

**Product Name:**

Model 30 pressure reducing valve with gagging device

**Special Features:**

Shock and vibration qualified by extension.

**Specification Data:**

81349 - mil-v-2042d government specification

**Specification Or Standard:**

Pe ii class 250 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A21100

**Mil-std (military Standard):**

Mil-v-1183 spec.