

View Online at <https://aerobasegroup.com/nsn/4820-01-525-2007>

Body Material:

Bronze, astm b61

Body Style:

Straight thru

Stem Material:

Nickel copper alloy

Furnished Items:

Union nut and tailpiece w/grooves

Media For Which Designed:

Water, fresh

First End Connection Type:

Unthreaded internal pipe

First End Style Designator:

Reduced socket with one brazing ring

First End Pipe Size Accommodated:

1.000 inches

Second End Relationship With First End:

Identical

Flow Control Device:

Disk

Flow Control Device Material:

Rubber, buna-n

End Connection Quantity:

2

Outlet Pressure Range:

+25.0/+60.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Spring

Outlet Pressure Setting:

40.000 pounds per square inch

End Application:

Cvn 77

End Connection Specification/std:

Mil-v-1183 with sbue 250 class

Valve Size:

1.000 inches

Product Name:

Model 30 pressure reducing valve with gagging device

Special Features:

Shock and vibration qualified by extension.

Specification Data:

81349 - mil-v-2042d government specification

Specification Or Standard:

Pe ii class 250 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100

Mil-std (military Standard):

Mil-v-1183 spec.