

View Online at <https://aerobasegroup.com/nsn/4820-01-526-8458>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Bolted

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Socket with brazing ring (tube) err-100

Valve Operation Method:

Automatic or manual

Connection Type:

Unthreaded internal tube all ends

Adjustable Pressure Range:

+20.0/+24.0 pounds per square inch

Maximum Operating Pressure:

400.0 pounds per square inch single response

Outside Diameter Tube Accommodated:

0.250 inches all ends

Product Name:

1/4" relief valve type 1741-t

Material:

Plastic polytetrafluoroethylene seat

Material Specification:

Astm b-61 assn standard all material responses body

Media For Which Designed:

Liquid single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever and 1 plugged drain and 2 tailpiece and 2 nut

Specification Data:

81349 - mil-v-24332 government specification

Specification Or Standard:

B grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.