NSN 4820-01-530-3343

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-530-3343

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+0.5/+150.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
8.0 pounds per square inch
Product Name:
Adjustable popoff relief valve
Special Features:
Adjustable poppet valve, zero leakage, out to atmoshere; temperature range determined my seal material
Material:
Stainless steel flow control device
Media For Which Designed:
Air single response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 deflector cap
Shelf Life:
N/a

NSN 4820-01-530-3343

Safety Relief Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0