

View Online at <https://aerobasegroup.com/nsn/4820-01-530-7072>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round all ends

Connection Type:

Flange all ends

Features Provided:

Manual override

Valve Size:

3.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

First Connection Face To Centerline Distance:

5.000 inches

Second Connection Face To Centerline Distance:

6.000 inches

Flange Face Design:

Plain all ends

Product Name:

3" relief valve, type 1792

Special Features:

Cast body with integral flanges iaw 20042 -150 lbs, drain iaw ms16142 1/2 tube o.D.; ven iaw ms16142 1/2 tube o.D.

Material:

Nickel alloy flow control device

Style Designator:

Err-090

Furnished Items And Quantity:

2 gasket

Specification Data:

81349 - mil-v-20065 government specification and 81349 - mil-f-20042 government specification

Specification Or Standard:

A-2 type and c class and 150 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-20065 spec.