## NSN 4820-01-532-2398

Globe Valve - Page 1 of 1

Mil-std (military Standard):

Mil-p-24583 spec.



View Online at https://aerobasegroup.com/nsn/4820-01-532-2398

Pipe Size Accommodated:
1.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Packing retaining
End Application:
Seawolf class ssn
Connection Style:
Socket all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Bonnet packing
Maximum Operating Pressure:
1250.0 pounds per square inch single response
Special Features:
Level iii valve
Material:
Rubber ethylene-propylene class epm packing
Material Specification:
Mil-p-24583 cl 2 gr n military specification 1st material response packing and mil-p-24503 ty ii cl 2 gr n military specification 2nd material
response packing and mil-r-83248 type 1 cl 1 military specification 3rd material response packing
Media For Which Designed:
Air single response
Style Designator:
Err-090
Test Data Document:
81349-mil-std-798 standard (includes industry or association standards, individual manufactureer standards, etc.). And 81349-mil-std-167-
standard (includes industry or association standards, individual manufactureer standards, etc.).
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
Yes - demil/mli
Fiig:
A046b0