

View Online at <https://aerobasegroup.com/nsn/4820-01-534-6584>

Pipe Size Accommodated:

0.250 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Renewable Seat Ring Type:

Retaining screw

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Minimum Operating Temp:

28.0 degrees fahrenheit

End Application:

Ws ssgn class submarine

Connection Style:

Socket (tube) all ends

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal tube all ends

Features Provided:

Bonnet packing

Outside Diameter Tube Accommodated:

0.250 inches all ends

Special Features:

Valve is designed for use with copper nickel tubing, classes 200, 700, 1650 and 3300 of mil-t-16420

Material:

Rubber fluorocarbon class fpm packing

Material Specification:

Qq-n-281 cl a form 2 federal specification single material response body

Style Designator:

Err-090

Test Data Document:

96906-mil-std-798 standard (includes industry or association standards, individual manufactureer standards, etc.). And 96906-mil-std-167-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0

Mil-std (military Standard):

Mil-g-22050 spec.