

View Online at <https://aerobasegroup.com/nsn/4820-01-535-8859>

Pipe Size Accommodated:

0.250 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Renewable Seat Ring Type:

Threaded

End Application:

W/s ohio class ssbn (trident)

Connection Style:

Socket all ends

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

1250.0 pounds per square inch single response

Special Features:

Level iii valve

Material:

Cobalt alloy seat

Material Specification:

Mil-p-24503 ty ii cl 2 or n military specification single material response packing and mil-p-24583 cl 2 or n military specification single material response packing

Style Designator:

Err-090

Test Data Document:

81349-mil-std-167-1 type i standard (includes industry or association standards, individual manufactureer standards, etc.). And 81349-mil-std-798 standard (includes industry or association standards, individual manufactureer standards, etc.).

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-p-24503 spec.