## NSN 4820-01-535-8859

Globe Valve - Page 1 of 2

A046b0



View Online at https://aerobasegroup.com/nsn/4820-01-535-8859

view offilite at https://defobasegroup.com/hsh/4020-01-000-0000
Pipe Size Accommodated:
0.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Renewable Seat Ring Type:
Threaded
End Application:
W/s ohio class ssbn (trident)
Connection Style:
Socket all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Bonnet packing
Maximum Operating Pressure:
1250.0 pounds per square inch single response
Special Features:
Level iii valve
Material:
Cobalt alloy seat
Material Specification:
Mil-p-24503 ty ii cl 2 or n military specification single material response packing and mil-p-24583 cl 2 or n military specification single material
response packing
Style Designator:
Err-090
Test Data Document:
81349-mil-std-167-1 type i standard (includes industry or association standards, individual manufactureer standards, etc.). And
81349-mil-std-798 standard (includes industry or association standards, individual manufactureer standards, etc.).
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

## NSN 4820-01-535-8859

Globe Valve - Page 2 of 2



Mil-std (military Standard):

Mil-p-24503 spec.