

View Online at <https://aerobasegroup.com/nsn/4820-01-536-6190>

**Pipe Size Accommodated:**

2.000 inches

**Overall Length:**

5.625 inches

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Threaded

**End Application:**

Lcs1

**Valve Operation Method:**

Manual

**Connection Type:**

Socket, weld, pipe

**Valve Size:**

2.000 inches

**Maximum Operating Pressure And Media For Which Designed:**

400.0 pounds per square inch water-oil-gas

**Stem Type:**

Nonrising

**Maximum Operating Temperature And Media For Which Designed:**

150.0 degrees fahrenheit water-oil-gas

**Inlet Relationship With Outlet:**

Identical

**Pressure Class:**

400.0 pounds per square inch

**Special Features:**

Rev w dated june 2005 added additional part number breakdown to differentiate metallic & rubber gasket, rubber gaskets, and o-rings. This valve has gaskets of nitrile for applications with service temperations up to 250 degrees suitable for use in steam, water, air and gas; valve is asbestos free; seat rings are coated iaw mil-std-1687

**Material:**

Nickel alloy disk

**Material Specification:**

Astm b61 assn standard single material response body

**Test Data Document:**

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-978 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No