NSN 4820-01-539-8999

Ball Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-539-8999 **Thread Direction:** Right-hand all ends **Bonnet Type:** Packing retaining **Renewable Seat Ring Type:** Pressed-in **Maximum Operating Temp:** 350.0 degrees fahrenheit single response **Minimum Operating Temp:** 0.0 degrees fahrenheit **End Application:** Water purification group **Connection Style:** G9 plain, optional en (pipe) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded internal pipe all ends **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Thread Size:** 2.000 inches all ends **Product Name:** Backwash three-way valve assembly **Special Features:** Tm 10-4610-241-24p c02 t.O. 40w4-13-44; brass ball and stem, packing, seals and thrust washer are ptfe/polytetrafluoroethylene; 2" 3-way full port diverter ball valve with adapter plug Material: Plastic polytetrafluoroethylene packing Media For Which Designed: Water-oil-gas single response **Style Designator:** A11 cross **Thread Series Designator:** Npt all ends **Furnished Items And Quantity:** 1 lever Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4820-01-539-8999

Ball Valve - Page 2 of 2



Fiig:

A046b0