NSN 4820-01-539-8999

Ball Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-539-8999

Thread Direction:

Right-hand all ends

Bonnet Type:

Packing retaining

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

350.0 degrees fahrenheit single response

Minimum Operating Temp:

0.0 degrees fahrenheit

End Application:

Water purification group

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Maximum Operating Pressure:

400.0 pounds per square inch single response

Thread Size:

2.000 inches all ends

Product Name:

Backwash three-way valve assembly

Special Features:

Tm 10-4610-241-24p c02 t.O. 40w4-13-44; brass ball and stem, packing, seals and thrust washer are ptfe/polytetrafluoroethylene; 2"

3-way full port diverter ball valve with adapter plug

Material:

Plastic polytetrafluoroethylene packing

Media For Which Designed:

Water-oil-gas single response

Style Designator:

A11 cross

Thread Series Designator:

Npt all ends

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-01-539-8999

Ball Valve - Page 2 of 2

Fiig: A046b0

