NSN 4820-01-540-4290

Gate Valve - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4820-01-540-4290 |
|---|
| Pipe Size Accommodated: |
| 3.000 inches |
| End Application: |
| Lpd-17 |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Butt weld pipe and flange, round w/o holes |
| Features Provided: |
| Bonnet packing |
| Valve Size: |
| 3.000 inches |
| Maximum Operating Pressure And Media For Which Designed: |
| 600.0 pounds per square inch steam |
| Stem Type: |
| Rising |
| Maximum Operating Tempurature And Media For Which Designed: |
| 775.0 degrees fahrenheit steam |
| Product Name: |
| 3" pressure seal gate valve |
| Inlet Relationship With Outlet: |
| Not identical |
| Pressure Class: |
| 600.0 pounds per square inch |
| Special Features: |
| Butt weld and flanged end connections iaw ansi b16.5; handwheel is provided |
| Material: |
| Steel uns k03504 body |
| Test Data Document: |
| 81349-mil-s-901 for medium weight grade a equipment; eq class i, fixture figure 9-12 & 10-1 specification (includes engineering type |
| bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, |
| and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that |
| are shown as "typical", "average", "", etc.). |
| Furnished Items And Quantity: |
| 1 handwheel |
| Specification Data: |
| 81349 - mil-v-18110 government specification |
| Specification Or Standard: |
| D composition |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Nic

Demilitarization:

NSN 4820-01-540-4290

Gate Valve - Page 2 of 2



Fiig:

A500a0