

View Online at <https://aerobasegroup.com/nsn/4820-01-541-6241>

Thread Direction:

Right-hand all ends

Flow Control Device:

Needle

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees fahrenheit

End Application:

Portable filtration cart assembly cfc124001a, model 912, cfc124002a, model 823

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Product Name:

Needle valve; inavy: valve, needle

Special Features:

End connections are: 1/4-18 nptf; flow 5 gpm; adjustment knob has both color and numeric indicators, 3 turns opens half-way, next 3 turns opens fully; seal material: nitrile

Material:

Steel comp 416 flow control device

Style Designator:

Err-090

Thread Series Designator:

Nptf all ends

Furnished Items And Quantity:

2 indicator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0