

View Online at <https://aerobasegroup.com/nsn/4820-01-545-7161>

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Renewable Seat Ring Type:**

Pressed-in

**Maximum Operating Temp:**

200.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-40.0 degrees fahrenheit

**End Application:**

Larc v

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded cartridge 1st end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

12 1st end

**Maximum Operating Pressure:**

5000.0 pounds per square inch single response

**Thread Size:**

1.625 inches 1st end

**Opening Pressure Setting:**

65.0 pounds per square inch

**Product Name:**

Check valve

**Special Features:**

Uses seal sk20-2

**Material:**

Steel

**Media For Which Designed:**

Oil single response

**Style Designator:**

Screw-in cartridge

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0