

View Online at <https://aerobasegroup.com/nsn/4820-01-545-7169>

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Spool

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

80.0 gallons per minute

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees fahrenheit

End Application:

Larc v

Valve Operation Method:

Automatic

Connection Type:

Threaded cartridge 1st end

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

1.312 inches 1st end

Opening Pressure Setting:

1500.0 pounds per square inch

Product Name:

Pilot operated spool-type relief valve

Special Features:

Tamper resistant cap; uses nitrile seal sk16-2

Material:

Steel

Media For Which Designed:

Oil 1st response

Surface Treatment:

Chromate zinc

Surface Treatment Specification:

Yellow zinc chromate mfr ref single treatment response

Style Designator:

Err-090

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0