

View Online at <https://aerobasegroup.com/nsn/4820-01-546-3419>

**Body Material:**

Bronze, mil-b-16541

**Body Style:**

Straight thru

**Stem Material:**

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

**First End Connection Type:**

Plain face flange

**First End Style Designator:**

Plain

**First End Flange Shape Style:**

Round w/ bolt holes

**Second End Relationship With First End:**

Identical

**Seat Material:**

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

**Face To Face Distance:**

8.500 inches

**Flow Control Device:**

Stem and integral disk and disk, dual

**Flow Control Device Material:**

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

**End Connection Quantity:**

2

**Two-way Valve Action:**

Reverse acting

**Capillary Tube Length:**

170.000 inches

**Bulb Material:**

Copper

**Temperature Adjustability:**

Adjustable

**Thermostatic Element:**

Liquid immersion type

**End Application:**

New construction lhd8

**Tempurature Rating:**

90.0 degrees fahrenheit

**End Connection Specification/std:**

Mil-f-20042

**Valve Size:**

2.500 inches

**Product Name:**

2-1/2" trac style a failsafe double seat reverse acting thermostatic temperature regulator valve assembly

**Special Features:**

Valve fails open; shock & vibration qualified by extension

**Specification Data:**

81349 - mil-v-19772 government specification

**Specification Or Standard:**

li type and 2 class and 250 series

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A21100

**Mil-std (military Standard):**

Mil-f-20042 spec.