

View Online at <https://aerobasegroup.com/nsn/4820-01-546-9195>

Thread Direction:

Right-hand 2nd end

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

6 1st end

Maximum Operating Temp:

280.0 degrees fahrenheit single response

Connection Style:

G46c plain (hose) 2nd end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Threaded external hose 2nd end

Thready Qty Per Inch (tpi):

7-1/2 2nd end

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

2.500 inches 2nd end

Outside Diameter:

6.125 inches 1st end

Thickness:

0.938 inches 1st end

Bolt Hole Diameter:

0.688 inches 1st end

Bolt Circle Diameter:

5.000 inches 1st end

Flange Face Design:

Plain 1st end

Material:

Rubber isobutylene-isoprene class iir flow control device

Media For Which Designed:

Water, fresh 1st response

Style Designator:

Err-090

Thread Series Designator:

Nh 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0