NSN 4820-01-548-5323

Safety Relief Valve - Page 1 of 2

Thread Class: 2b all ends

Thread Direction:



View Online at https://aerobasegroup.com/nsn/4820-01-548-5323

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
32.0 gallons per minute
End Application:
New construction ssn774
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Thready Qty Per Inch (tpi):
12 all ends
Adjustable Pressure Range:
+1400.0/+2300.0 pounds per square inch
Thread Size:
1.062 inches all ends
Product Name:
Inavy: valve, hyrdaulic relief
Material:
Stainless steel body
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Style Designator:
Err-090
Thread Series Designator:
Un all ends
Specification Data:
96906 - ms28893 government specification
Specification Or Standard:
C12 number
Departure From Cited Document:
Modified by end connections 1.063-12un-2b
Shelf Life:

N/a

NSN 4820-01-548-5323

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0