NSN 4820-01-548-5323

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-548-5323

Thread Class:

2b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

32.0 gallons per minute

End Application:

New construction ssn774

Connection Style:

G4 gasket sea (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss all ends

Thready Qty Per Inch (tpi):

12 all ends

Adjustable Pressure Range:

+1400.0/+2300.0 pounds per square inch

Thread Size:

1.062 inches all ends

Product Name:

Inavy: valve, hyrdaulic relief

Material:

Stainless steel body

Media For Which Designed:

Hydraulic fluid, petroleum base single response

Style Designator:

Err-090

Thread Series Designator:

Un all ends

Specification Data:

96906 - ms28893 government specification

Specification Or Standard:

C12 number

Departure From Cited Document:

Modified by end connections 1.063-12un-2b

Shelf Life:

N/a

NSN 4820-01-548-5323

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

