

View Online at <https://aerobasegroup.com/nsn/4820-01-549-4762>

Body Material:

Bronze, mil-b-16541

Body Style:

Straight thru

Stem Material:

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

Furnished Items:

Tailpiece w/grooves and union nut

First End Connection Type:

Unthreaded internal pipe

First End Style Designator:

Socket w/brazing ring

First End Pipe Size Accommodated:

1.500 inches

Second End Relationship With First End:

Identical

Seat Material:

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

Face To Face Distance:

7.750 inches

Flow Control Device:

Disk, dual

Flow Control Device Material:

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

End Connection Quantity:

2

Renewable Seat Ring Type:

Threaded

Two-way Valve Action:

Reverse acting

Capillary Tube Length:

300.000 inches

Bulb Material:

Copper

Tempurature Adjustability:

Adjustable

Thermostatic Element:

Liquid immersion type

End Application:

Hsu hydraulic starting power

Tempurature Rating:

Between 130.0 degrees fahrenheit and 160.0 degrees fahrenheit

End Connection Specification/std:

Mil-f-1183 grooved for brazing rings

Valve Size:

1.500 inches

Product Name:

Regualtor valve assembly, 1-1/2" style a failsafe, doulble seat, reverse acting

Special Features:

Set temperature: 140; flow 45 gpm

Specification Data:

81349 - mil-v-19772 government specification

Specification Or Standard:

li type and 2 class and 250 series and a design

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A21100

Mil-std (military Standard):

Mil-f-1183 spec.