

View Online at <https://aerobasegroup.com/nsn/4820-01-549-4762>

**Body Material:**

Bronze, mil-b-16541

**Body Style:**

Straight thru

**Stem Material:**

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

**Furnished Items:**

Tailpiece w/grooves and union nut

**First End Connection Type:**

Unthreaded internal pipe

**First End Style Designator:**

Socket w/brazing ring

**First End Pipe Size Accommodated:**

1.500 inches

**Second End Relationship With First End:**

Identical

**Seat Material:**

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

**Face To Face Distance:**

7.750 inches

**Flow Control Device:**

Disk, dual

**Flow Control Device Material:**

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

**End Connection Quantity:**

2

**Renewable Seat Ring Type:**

Threaded

**Two-way Valve Action:**

Reverse acting

**Capillary Tube Length:**

300.000 inches

**Bulb Material:**

Copper

**Tempurature Adjustability:**

Adjustable

**Thermostatic Element:**

Liquid immersion type

**End Application:**

Hsu hydraulic starting power

**Tempurature Rating:**

Between 130.0 degrees fahrenheit and 160.0 degrees fahrenheit

**End Connection Specification/std:**

Mil-f-1183 grooved for brazing rings

**Valve Size:**

1.500 inches

**Product Name:**

Regualtor valve assembly, 1-1/2" style a failsafe, doulble seat, reverse acting

**Special Features:**

Set temperature: 140; flow 45 gpm

**Specification Data:**

81349 - mil-v-19772 government specification

**Specification Or Standard:**

li type and 2 class and 250 series and a design

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A21100

**Mil-std (military Standard):**

Mil-f-1183 spec.