

View Online at <https://aerobasegroup.com/nsn/4820-01-551-2661>

Thread Class:

2a all ends

Thread Direction:

Right-hand all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees fahrenheit

End Application:

ASSA-UL-TAM-PHIB

Connection Style:

Swivel nut, flareless (tube) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal tube all ends

Mounting Position:

Vertical

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Product Name:

Flow regulator, in-line

Special Features:

20 gpm flow capacity; flow from left side (1) to right side (2) is allowed with 50 psi back pressure; flow from (2) to (1) is blocked with a mechanism to assist in static and low load conditions; length is 3.00 inches ; hex diameter is 1.000 inches ; female o-ring ports; part is for fixed displacement hydraulic circuit application

Material:

Steel body lining

Media For Which Designed:

Oil, hydraulic single response

Style Designator:

Straight thru

Specification Data:

81343 - sae j1926 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0