NSN 4820-01-551-2812

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-551-2812 Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 738.0 gallons per minute **Maximum Operating Temp:** 1500.0 degrees fahrenheit single response **Minimum Operating Temp:** 1500.0 degrees fahrenheit **End Application:** Overhaul/availability lpd13/wk it 255-21-002 **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 2.000 inches **Maximum Operating Pressure:** 6250.0 pounds per square inch single response **Opening Pressure Setting:** 920.0 pounds per square inch Flange Face Design: Raised straight all ends **Product Name:** Relief valve **Special Features:** Application: feed water; 2" x 3" angle valve with semi-nozzle inlet with h size orifice seat; flanges iaw aisi cl600 inlet and cl150 outlet Material:

Steel body

Media For Which Designed:

Liquid single response

Style Designator:

Err-090

Shelf Life:

N/a

NSN 4820-01-551-2812

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0