NSN 4820-01-556-8005

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-556-8005

view Online at https://aerobasegroup.com/nsn/4820-01-556-8005
Pipe Size Accommodated:
0.750 inches all ends
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
172.8 cubic feet per minute
Renewable Seat Ring Type:
Retaining screw
Maximum Operating Temp:
425.0 degrees fahrenheit single response
End Application:
Overhaul/availability cvn70
Connection Style:
Socket all ends
Valve Operation Method:
Automatic or manual
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+23.0 to 45.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Special Features:
Valve provided with gagging device, bonnet plug, adjusting ring pin; disc insert material polytetrafluoroethylene; o-ring material viton
Material:
Stainless steel
Media For Which Designed:
Air single response
Style Designator:
C1 angle
Furnished Items And Quantity:
1 lever and 2 tailpiece and 2 nut
Specification Data:
Mil-v-22549d government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-01-556-8005

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-v-22549 spec.