NSN 4820-01-560-2649

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-560-2649

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Minimum Operating Temp:

-20.0 degrees fahrenheit

End Application:

Cg52

Connection Style:

G42 flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.438 inches 1st end

Opening Pressure Setting:

8.0 pounds per square inch

Product Name:

Adjustable relief valve .5-150.0 psi

Special Features:

Inlet male tube iaw as4395 with no cone point, out to atmosphere with deflector cap; seal material: viton

Material:

Steel comp 316 body

Media For Which Designed:

Air single response

Style Designator:

Err-090

Thread Series Designator:

Unjf 1st end

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

NSN 4820-01-560-2649

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

