

View Online at <https://aerobasegroup.com/nsn/4820-01-561-7296>

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

75186.0 pounds per hour

Bolt Hole Quantity:

12 2nd end

Maximum Operating Temp:

775.0 degrees fahrenheit single response

End Application:

Cvn77

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Adjustable Pressure Range:

+71.0/+83.0 pounds per square inch

Maximum Operating Pressure:

100.0 pounds per square inch single response

Outside Diameter:

16.500 inches 2nd end

First Connection Face To Centerline Distance:

9.500 inches

Bolt Hole Diameter:

1.120 inches 1st end

Second Connection Face To Centerline Distance:

9.440 inches

Bolt Circle Diameter:

13.750 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Product Name:

Angle relief valve

Special Features:

Inlet is 6.000 inches with nozzle. Outlet is 8.000 inches.

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0