## NSN 4820-01-564-0918

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-564-0918

Thread Class:

**Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Minimum Operating Temp:** 100.0 degrees fahrenheit **End Application:** Camera cannister, remote multi-mission vehicle **Connection Style:** G49d gasket seal (gas fitting) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss 1st end Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 1.062 inches 1st end **Opening Pressure Setting:** 7.6 pounds per square inch **Product Name:** Relief valve **Special Features:** Threaded connection per as4395e12; 3/4 inch valve Material: Plastic polytetrafluoroethylene seat **Style Designator:** Err-090 **Thread Series Designator:** Unj 1st end Shelf Life:

N/a
Unit Of Measure:

## NSN 4820-01-564-0918

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0