## NSN 4820-01-570-8367

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-570-8367

**Thread Direction:** Right-hand 1st end **Flow Control Device:** Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Pressure seal, ring type **Disk Loading Method:** Spring Valve Discharge Flow Rate: 31.0 gallons per minute Maximum Operating Temp: 406.0 degrees fahrenheit single response **Minimum Operating Temp:** -60.0 degrees fahrenheit **Connection Style:** G9 plain, optional en (pipe) 2nd end Valve Operation Method: Automatic **Connection Type:** Threaded internal pipe 2nd end Maximum Operating Pressure: 300.0 pounds per square inch single response **Thread Size:** 1.250 inches 2nd end **Opening Pressure Setting:** 25.0 pounds per square inch **Product Name:** Relief valve **Special Features:** Pressure tight cap; commercial valve; replaces 20-1 1/4-2s Material: Bronze Media For Which Designed: Liquid single response **Style Designator:** Err-090 **Thread Series Designator:** Npt 1st end Shelf Life:

N/a

## NSN 4820-01-570-8367

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

