

View Online at <https://aerobasegroup.com/nsn/4820-01-571-5029>

Pipe Size Accommodated:

0.555 inches all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees fahrenheit

End Application:

New construction ssn 782

Connection Style:

Socket (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Unthreaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Opening Pressure Setting:

5.0 pounds per square inch

Product Name:

In-line check valve, .250 i.P.S

Special Features:

Shock and vibration qualified; similar to type 1 and 2 air service valves except for o-ring material

Material:

Steel comp 316 seat

Material Specification:

Qq-s-763. type 316 federal specification 1st material response flow control device and kel-f fluorocarbon mfr ref 2nd material response flow control device

Media For Which Designed:

Air single response

Style Designator:

Straight thru

Furnished Items And Quantity:

2 nut and 2 tailpiece

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A530b0