NSN 4820-01-572-6359

Globe Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-572-6359

| Bonnet Type: |
|--|
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 4 all ends |
| End Application: |
| New construction lpd22 |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 2.500 inches |
| Outside Diameter: |
| 7.000 inches all ends |
| Face To Face Distance: |
| 8.500 inches |
| Thickness: |
| 0.690 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 5.000 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.060 inches all ends |
| Raised Face Diameter: |
| 4.130 inches all ends |
| Material: |
| Stainless steel stem |
| Material Specification: |
| Astm a351-cf8m assn standard single material response body |
| Style Designator: |
| Err-090 |
| Furnished Items And Quantity: |
| 1 handwheel |

NSN 4820-01-572-6359

Globe Valve - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0