## NSN 4820-01-573-6223

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-573-6223

Slide  Disk Loading Method: Spring  End Application:  606876400 lube oil pump unit  Valve Operation Method: Automatic  Mounting Position: Horizontal or vertical  Maximum Operating Pressure: 5000.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch  Product Name: Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Filig: Holisch  Filig: Hol	Flow Control Device:
Spring  End Application:  060876400 lube oil pump unit  Valve Operation Method:  Automatic  Mounting Position:  Horizontal or vertical  Maximum Operating Pressure:  5000.0 pounds per square inch single response  Opening Pressure Setting:  4.0 pounds per square inch  Product Name:  Valve, check  Special Features:  Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator:  Screw-in cartridge  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Figi:	Slide
End Application:  060876400 lube oil pump unit  Valve Operation Method:  Automatic  Mounting Position:  Horizontal or vertical  Maximum Operating Pressure:  5000.0 pounds per square inch single response  Opening Pressure Setting:  4.0 pounds per square inch  Product Name:  Valve, check  Special Features:  Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator:  Screw-in cartridge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Figi:	Disk Loading Method:
000876400 lube oil pump unit  Valve Operation Method: Automatic  Mounting Position: Horizontal or vertical  Maximum Operating Pressure: 5000.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch Product Name: Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Figi:	Spring
Valve Operation Method: Automatic  Mounting Position: Horizontal or vertical  Maximum Operating Pressure: 5000.0 pounds per square inch single response  Fopening Pressure Setting: 4.0 pounds per square inch Product Name: Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Figi:	End Application:
Automatic  Mounting Position: Horizontal or vertical  Maximum Operating Pressure: 5000.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch  Product Name:  Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Figi:	060876400 lube oil pump unit
Mounting Position: Horizontal or vertical  Maximum Operating Pressure: 5000.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch  Product Name:  Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Figs:	Valve Operation Method:
Horizontal or vertical  Maximum Operating Pressure: 5000.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch  Product Name:  Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Figs:	Automatic
Maximum Operating Pressure: 5000.0 pounds per square inch single response Opening Pressure Setting: 4.0 pounds per square inch Product Name: Valve, check Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Figs:	Mounting Position:
5000.0 pounds per square inch single response  Opening Pressure Setting: 4.0 pounds per square inch  Product Name:  Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Horizontal or vertical
Opening Pressure Setting:  4.0 pounds per square inch  Product Name:  Valve, check  Special Features:  Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator:  Screw-in cartridge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Maximum Operating Pressure:
4.0 pounds per square inch  Product Name:  Valve, check  Special Features:  Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator:  Screw-in cartridge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	5000.0 pounds per square inch single response
Product Name:  Valve, check  Special Features:  Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator:  Screw-in cartridge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Opening Pressure Setting:
Valve, check  Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4.0 pounds per square inch
Special Features: Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Product Name:
Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil  Style Designator:  Screw-in cartridge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Valve, check
Style Designator: Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Screw-in cartridge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Threaded cartridge valve, 4820-01-522-1363, in aluminum body/housing with sae 10 threaded ports, p/n dak; media lube oil
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Screw-in cartridge
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A530b0	Fiig:
	A530b0