

View Online at <https://aerobasegroup.com/nsn/4820-01-576-2428>

Body Material:

Bronze, astm b61

First End Flange Outside Diameter:

2.875 inches

Body Style:

Straight thru

Media For Which Designed:

Water, salt

First End Connection Type:

Plain face flange

First End Style Designator:

Plain

First End Flange Shape Style:

Round w/ bolt holes

First End Flange Thickness:

0.938 inches

First End Bolt Hole Quantity:

6

First End Bolt Hole Diameter:

0.688 inches

Face To Face Distance:

11.750 inches

Flow Control Device:

Disk

Flow Control Device Material:

Rubber, buna-n

End Connection Quantity:

2

Outlet Pressure Range:

+100.0/+150.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Stem Design:

Single seat

Valve Loading Method:

Spring

Filter:

Not included

End Application:

Lsd44 midlife s/a 3290.4k

Temperature Rating:

165.0 degrees fahrenheit

End Connection Specification/std:

Mil-f-20042

Valve Size:

2.500 inches

Product Name:

Sea water pressure reducing valve

Specification Data:

81346-astm f1370 professional/industrial association specification

Specification Or Standard:

1 type and j size and f end and 2 rating and x range

Departure From Cited Designator:

250.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100

Mil-std (military Standard):

Mil-f-20042 spec.