

View Online at <https://aerobasegroup.com/nsn/4820-01-578-3750>

Flow Control Device:

Poppet

Bolt Hole Quantity:

4 1st end

Maximum Operating Temp:

450.0 degrees fahrenheit single response

End Application:

F-15sg strike eagle

Connection Style:

Beaded (hose) 2nd end

Width:

2.440 inches 1st end

Length:

2.440 inches 1st end

Valve Operation Method:

Automatic

Flange Shape:

Rectangular with holes 1st end

Connection Type:

Unthreaded external hose 2nd end

Mounting Position:

Horizontal

Maximum Operating Pressure:

90.0 pounds per square inch single response

Thickness:

0.250 inches 1st end

Bolt Hole Diameter:

0.285 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.812 inches 1st end

Center To Center Distance Between Bolt Holes Along Width:

1.812 inches 1st end

Flange Face Design:

Plain 1st end

Product Name:

Valve, check - hot air

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-6, alloy 2024 federal specification single material response

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.