## NSN 4820-01-584-9721

Globe Valve - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/4820-01-584-9721

Pipe Size Accommodated:
1.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Packing retaining
Maximum Operating Temp:
250.0 degrees fahrenheit single response
End Application:
New construction cvn78
Connection Style:
Socket with brazing ring all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Maximum Operating Pressure:
400.0 pounds per square inch single response
Product Name:
1-1/4" brz sil-braza union end globe valve
Special Features:
Shock qualified; tailpieces iaw 53711-803-7063850 b6-1 (union seals to be supplied by northrop grumann newport news)
Material:
Plastic polytetrafluoroethylene flow control device
Media For Which Designed:
Water-oil-gas 1st response
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel and 2 tailpiece and 2 nut
Specification Data:
80064-803-4384536 government specification
Specification Or Standard:
6 size and 1 type
Departure From Cited Document:
Modified by bonnet o-ring material of fluorocarbon iaw ams-r-83248, type 1 cl 1 and handwheel nut material of low-lead brass
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

## NSN 4820-01-584-9721

Globe Valve - Page 2 of 2



Fiig:

A046b0