## NSN 4820-01-619-5916

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-619-5916 **Thread Class:** 2 all ends **Thread Direction:** Right-hand all ends **Bonnet Type:** Inside spring **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Minimum Operating Temp:** 406.0 degrees fahrenheit **End Application:** Sentinel class fast response cutter b (frc-b) **Connection Style:** G9 plain, optional en (pipe) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 2nd end Thready Qty Per Inch (tpi): 11.5 2nd end **Thread Size:** 2.0 inches 2nd end **Opening Pressure Setting:** 20.0 pounds per square inch **Special Features:** Cms data id 2732 pccn se0640 plisn a001; this valve reated by underwriters laboratories for oil services Material: Copper alloy 844 disk **Material Specification:** Astm b62 assn standard single material response body **Style Designator:** A12 angle **Thread Series Designator:** Npt 1st end Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4820-01-619-5916

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0