Fluid Pressure Regulating Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-620-8009

StelPody Style:Drop: natridgeMetarMetar First End Connection Type:Threaded cartridgeFirst End Thread Size And Series/type Designator:0.5 nptFord Connection Quentity:PoppetEnd Connection Quentity:1Regulation Type:Automatic single stageValve Loading Method:SpringMaximun Intel Pressure Rating:15.0 pounds per square inchOutler Pressure Accuracy Rating:16.1 pressure Accuracy Rating:17.1 pressure Stafe Internet I
Dro-in artridge           Media For Which Designed:           Water           First End Connection Type:           Threaded cartridge           First End Thread Size And Series/type Designator:           0.5 npt           Flow Control Device:           Poppet           End Connection Quantity:           1           Regulation Type:           Automatic single stage           Valve Loading Method:           Spring           Maximum Intel Pressure Rating:           150.0 pounds per square inch           Outlet Pressure Accuracy Rating:           5.0 pounds per square inch           Filter:           Not included           Tempurature Rating:           Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit           Product Name:           Series 05 mini water hammer arrestor           Special Features:           Iter           Valut Of Measure:           Valut           Unit of Measure:           Na           Demilitarization:           No           Filer:
Heria For Which Designed:         Water         First End Connection Type:         Threaded cartridge         First End Thread Size And Series/type Designator:         0.5 npt         Flow Control Device:         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         15.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Porduct Name:         Series 05 mini water hammer arrestor         Special Features:         Item         Valve         Unit Of Measure:         Na         Unit Of Measure:         Na         Unit Cold Measure:         Na         Dimiliarization:         No         File:
Water         First End Connection Type:         Threaded cartridge         First End Thread Size And Series/type Designator:         0.5 npt         Flow Control Device:         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Intel Pressure Rating:         15.0.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Solo pounds per square inch         Filter:         Not included         Tempurature Rating:         Solo pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Sheff Life:         Na         Chot Measure:         Image:       Imag
First End Connection Type:         Threaded cartridge         First End Thread Size And Series/type Designator:         0.5 npt         Flow Control Device:         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         15.0.0 pounds per square inch         Duttet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Shelf Life:         N/a         Lift Of Measure:         -         -         No         No         Filter:         N/a         Euter Faures:         Product Name:         Euter Faures:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end <td< td=""></td<>
Threaded cartridge         First End Thread Size And Series/type Designator:         0.5 npt         Flow Control Device:         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         10.0 pounds per square inch         Outlet Pressure Accuracy Rating:         10.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Botwen 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Ith Infer         Na         Did Measure:         Na         Suid Measure:
First End Thread Size And Series/type Designator:         0.5 npt         Flow Control Device:         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Intel Pressure Rating:         15.0 pounds per square inch         Dottel Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Temparature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         N/a         Line Measure:         N/a         Did Measure:         N/a         Filter:         N/a         Did Measure:         N/a         Euric Measure:
0.5 npt         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Shelf Life:         N/a         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Shelf Life:         N/a         Itin Of Measure:               Pomilitarization:         No         Fig:
Flow Control Device:         Poppet         End Connection Quantity:         1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Ferueration Rating:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Maximum         Valu         Dentiltarization:         Image:
Poppet End Connection Quantity: 1 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Accuracy Rating: 5.0 pounds per square inch Outlet Pressure Accuracy Rating: 5.0 pounds per square inch Filter: Not included Fempurature Rating: Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit Product Name: Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure: - Demilitarization: No
A         Faculation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Intet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Steries 05 mini water hammer arrestor         Special Features:         Nda         Life         N/a         Ditt Of Measure:         Image:         Image:         Image:         Image:
1         Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Sheff Life:         N/a         Demilitarization:         Formation:         Fig:
Regulation Type:         Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Sheff Life:         N/a         Demilitarization:         r         Find         Fig:
Automatic single stage         Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Sprieg OF mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Shelf Life:         N/a         Init Of Measure:         Image:         Image:
Valve Loading Method:         Spring         Maximum Inlet Pressure Rating:         150.0 pounds per square inch         Outlet Pressure Accuracy Rating:         5.0 pounds per square inch         Filter:         Not included         Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Shelf Life:         N/a         Init Of Measure:            Init Of Measure:            Fig:
Spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Accuracy Rating: 5.0 pounds per square inch Filter: Not included Tempurature Rating: Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit Product Name: Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:
Maximum Inlet Pressure Rating:150.0 pounds per square inchOutlet Pressure Accuracy Rating:5.0 pounds per square inchFilter:Not includedTempurature Rating:Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheitProduct Name:Series 05 mini water hammer arrestorSpecial Features:Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one endShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:
150.0 pounds per square inch Outlet Pressure Accuracy Rating: 5.0 pounds per square inch Filter: Not included Tempurature Rating: Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit Product Name: Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:
Outlet Pressure Accuracy Rating:5.0 pounds per square inchFilter:Not includedTempurature Rating:Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheitProduct Name:Series 05 mini water hammer arrestorSpecial Features:Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one endShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:
5.0 pounds per square inch Filter: Not included Tempurature Rating: Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit Product Name: Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:
Filter:Not includedTempurature Rating:Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheitProduct Name:Series 05 mini water hammer arrestorSpecial Features:Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one endShelf Life:N/aDuit Of Measure:Demilitarization:NoFig:
Not included <b>Tempurature Rating:</b> Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit <b>Product Name:</b> Series 05 mini water hammer arrestor <b>Special Features:</b> Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end <b>Shelf Life:</b> N/a <b>Dunit Of Measure:</b> Demilitarization:         No         Fig:
Tempurature Rating:         Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit         Product Name:         Series 05 mini water hammer arrestor         Special Features:         Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end         Shelf Life:         N/a         Duit Of Measure:            Demilitarization:         No         Fig:
Between 33.0 degrees fahrenheit and 180.0 degrees fahrenheit Product Name: Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:
Product Name: Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure:  Demilitarization: No
Series 05 mini water hammer arrestor Special Features: Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:
Special Features:   Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:
Item has an air preload of 60 psi; dims are 1.250 inch diameter x 5.500 inch long with 1/2 npt on one end Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:
N/a Unit Of Measure:  Demilitarization: No Fiig:
Unit Of Measure:  Demilitarization: No Fiig:
 Demilitarization: No Fiig:
No Fiig:
No Fiig:
Fiig:
-
A21100