NSN 4820-01-624-7792

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-624-7792

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
120.0 degrees celsius single response
Minimum Operating Temp:
-20.0 degrees celsius
Connection Style:
Plain (screw-in cartridge) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded cartridge 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
14 1st end
Maximum Operating Pressure:
350.0 bar single response
Thread Size:
0.875 inches 1st end
Opening Pressure Setting:
1.03 bar
Product Name:
Poppet type screw-in cartridge check valve
Special Features:
Viton seals
Material:
Aluminum body
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Screw-in cartridge
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a

NSN 4820-01-624-7792

Check Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A530b0